


PRODUKT INFORMATION MARKISVÄV

Bredd:	120 cm
Rivstyrka varp:	1570,7 N (UNI EN ISO 13934-1)
Rivstyrka väft:	864 N (UNI EN ISO 13934-1)
Garn nr:	NE 20/2
Impregnering:	TEFLON (UNI EN 24920)
Konstruktion, varp/väft:	31 - 14 /cm ²
Komposition:	100% spinnfärgad acryl
Ljushärdighet:	7 - 8 (UNI EN ISO 105-B03)
Vattentäthet:	>300 mm (UNI EN 20811)
Vikt väv:	300 gr/m ²

		SCHEDA ARTICOLO				N° PSQ 008/06 Edizione 01 Rev.00 Data 1°em.25/05/2002	
Data : 10/07/2002		Articolo: TEMPOTEST STAR TREND STYLE				Scheda nr. 046	
CARATTERISTICA VALUTATA CHARACTERISTICS HAUPTMERKMALE CARACTERISTIQUES	UNITA' DI MISURA UNIT MASSEINHEIT UNITÉ	RISULTATI OTTENUTI SUI CAMPIONI RESULTS ERGEBNISSE RESULTATS				RIF. NORME	
Altezza pezza / Width Stückbreite/ Largeur	Cm	120					
Peso tessuto / Weight Gewicht/ Poids	gr/m ²	300 (+ - 5%)					
Ordito/Warp /Kette/Chaîne	Fili/cm. – Ends/inch – Fäden/cm - Fils/cm.	31					
	Titolo / Count / Garnnummer / Titre	Ne 20/2					
Trama/Weft / Schuß/Trame	Trame/cm. – Picks/inch – Fäden/cm - Fils/cm.	14					
	Titolo / Count / Garnnummer / Titre	Ne 20/2					
Composizione / Composition Zusammensetzung / Composition	%	100% Fibra Acrilica outdoor tinta in massa					
Carico alla rottura / Breaking load Reißfestigkeit / Charge de rupture	N	Ordito/Warp /Kette/Chaîne	1570,7	Trama/Weft Schuß/Trame	864	UNI EN ISO 13934 – 1	
	Allungamento %	Ordito/Warp /Kette/Chaîne	28,6%	Trama/Weft Schuß/Trame	28,9%		
Impermeabilità / Impermeability / Wasserdichte / Imperméabilité		Idrorepellente / water-repellent / wasserabstossend / hydrofuge				UNI EN 24920	
Colonna d'acqua / Water column / Wassersäule / Colonne d'eau	Mm	>300				UNI EN 20811	
Solidità dei colori alle intemperie con esposizione all'aperto : Fading resistance to the sun and the weather conditions : Lichtechtheit der Farben im Freien : Tenue des couleurs aux intempéries:		grado 7/8 – 8 colori tinti in massa Vedi garanzia 5 anni 7/8 – 8 degree solution dyed colours See 5 year guarantee 7/8 – 8 bei spinddüsengefärbten Farben Siehe 5 Jahre Garantie degré 7/8 – 8 coloris teints dans la masse Voir garantie de 5 ans				UNI EN ISO 105 – B 03	
Finissaggio: Finishing: Ausrüstung: Finissage:	Antimacchia, imputrescibile, idro-oleorepellente con trattamento Teflon. Soil-resistant, mould resistant, oil and water-repellent with Teflon finishing Fleck-, wasser- und ölabbstossend, fäulnisverhütend mit Teflon Anti-tache, imputrescible, repoussant à l'huile avec finissage Teflon						
